

Mabanol Xenon Alpha Classic 15W-40

Universal Multigrade Engine Oil

Application

Mabanol Xenon Alpha Classic 15W-40 was developed for universal use and is suitable for mixed vehicle fleets and construction industry operations. The performance of this multi-grade engine oil meets the requirements commercial and passenger car diesel engines as well as that of petrol engines with or without turbochargers.

Properties

Mabanol Xenon Alpha Classic 15W-40 is a multigrade engine oil suited for use in diesel and petrol engines. The 15W-40 viscosity range ensures good fluidity and excellent cold starts in winter and high temperature stability even under extreme loads.

High-quality base oils together with selected additives will ensure excellent anti-wear properties and engine cleanliness. The formation of black sludge will also be avoided.

Specifications

- SAE Grade 15W-40
- ACEA A3/B3
- API SL/CG-4

Recommended for

- MB-Sheet 229.1

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,883
Dyn. Viscosity at -20°C	ASTM D 5293	mPa s	6.380
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	102
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	13,8
Viscosity Index (VI)	DIN ISO 2909		133
Flash point COC	DIN ISO 2592	°C	236
Pourpoint	DIN ISO 3016	°C	-39

Updated in March 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981